

THE COMPLETE LINE OF D.O.E. APPROVED IN-GROUND PUMPS



IN-GROUND PUMPS

Model #	Total HP	Description	WEF (Weighted Energy Factor)
PD-270	2.7	2.7 THP, Variable Speed	7.253
PD-270A	2.7	2.7 THP, Variable Speed SVL	7.716
PD-225	2.25	2.25 THP, Variable Speed	7.460
PD-165	1.65	1.65 THP, Variable Speed, Dual Voltage	7.796
PD-110	1.10	1.10 THP, Single Speed	4.11
WB075	1.25	1.25 THP, Booster Pump	.502

THE COMPLETE LINE OF D.O.E. APPROVED ABOVE GROUND PUMPS



ABOVE GROUND PUMPS			
Model #	HP SPL	Description	WEF (Weighted Energy Factor)
CD-07-1-N	1.0	Center Discharge, with 3' NEMA Cord	3.887
CD-07-1-T	1.0	Center Discharge, with 3' Twist Lock Cord	3.887
CD-10-1-N	2.0	Center Discharge, with 3' NEMA Cord	3.632
CD-10-1-T	2.0	Center Discharge, with 3' Twist Lock Cord	3.632
SD-07-1-N*	1.0	Hi-Flo II, Side Discharge, with 3' NEMA Cord	3.99
SD-07-1-T*	1.0	Hi-Flo II, Side Discharge, with 3' Twist Lock Cord	3.99
SD-10-1-N*	2.0	Hi-Flo II, Side Discharge, with 3' NEMA Cord	3.759
SD-10-1-T*	2.0	Hi-Flo II, Side Discharge, with 3' Twist Lock Cord	3.759
SD-07-2-N*	1.0	2-Speed Hi-Flo II, Side Discharge, with 3' NEMA Cord	6.158
SD-07-2-T*	1.0	2-Speed Hi-Flo II, Side Discharge, with 3' Twist Lock Cord	6.158
SD-10-2-N*	2.0	2-Speed Hi-Flo II, Side Discharge, with 3' NEMA Cord	6.059
SD-10-2-T*	2.0	2-Speed Hi-Flo II, Side Discharge, with 3' Twist Lock Cord	6.059

*NOTE: For Horizontal Hi-Flo II, need to add a " - H " at the end of the above Hi Flo II part numbers.