GENERAL CERTIFICATE OF COMPLIANCE

32" DIAMOND STRIP DRAIN - CONCRETE: P/N 640-136x V

| Contents: | 1 | |
|--|---|---|
| Part Number: | 640-136x V | |
| Description: Size: | Diamond Strip Drain - Concrete 32" | |
| Floor Flow Rate: Wall Flow Rate: Wall Flow Rate: | 244 GPM (one port center) 320 GPM (two ports) 216 GPM (one port center) 216 GPM (two ports) | NSF. VGBA |
| Date | of Manufacture: | 2017 |
| Date of | Installation: | |
| Name o | f Installer: | |
| Signature of Installer: | | |
| Graham Baker Pool and S 734-769-8670. Testing re | ted, certified and listed to the requirements of ANSI/AP pa Safety Act. Certified by: NSF International, Inc., 729 N port from May, 2021. This product is certified to comply a Safety Act. A copy of the test results for the above may | I. Dixboro Rd., Ann Arbor, MI 48105, with §1404 of the Virginia Graham Baker |

go to: www.nsf.org.

The test results supporting the product certification are maintained by Ray Mirzaei, 2200 Sturgis, Rd, Oxnard , CA 93030 **Phone**: 805-9810262 **Email**: raym@waterwayplastics.com

This product is manufactured by Waterway Plastics, Oxnard CA 93030





2200 East Sturgis Road Oxnard CA 93030 • Phone 805.981.0262 • Fax 805.981.9403 waterway@waterwayplastics.com • www.waterwayplastics.com