GENERAL CERTIFICATE OF COMPLIANCE

32" DIAMOND STRIP DRAIN - FIELD BUILT SUMPS: P/N 640-137x V

Contents:	1	
Part Number:	640-137x V	
Description: Size:	Diamond Strip Drain - Field Built Sur 32″	nps
Open Area: GPM @ 1.5 fps:	24 in ² 111	
Floor Flow Rate:	244 GPM (one port center) 320 GPM (two ports) 216 GPM (one port center)	NSF.
Wall Flow Rate:	216 GPM (two ports) of Manufacture:	VGBA 2017
Date of	Installation:	
Name	of Installer:	
Signati	ire of Installer:	
	sted to ANSI/ASME 112.19.8-2007 (ANSI/APSP - 16. 2017) per § Certified by: NSF International, Inc., 729 N. Dixboro Rd., Ann Arb ry of 2021.	
	o comply with \$1404 of the Virginia Graham Baker (VGBA 2017) ove may be found at www.waterwayplastics.com or go to wwv	
	ng the product certification are maintained by Ray Mirzaei, 2200 nail: raym@waterwayplastics.com) Sturgis, Rd, Oxnard , CA 93030
This product is manufact	ured by Waterway Plastics, Oxnard, CA 93030 USA	





2200 East Sturgis Road Oxnard CA 93030 • Phone 805.981.0262 • Fax 805.981.9403 waterway@waterwayplastics.com • www.waterwayplastics.com